

LED NEON FLEX STRIP LIGHTING




Features: Ultra Thin and Flat Shape, Super Flexible and Bright (Up to 150LM per meter)

1. High Brightness SMD3014 LED as light source
2. First-class, eco-friendly & UV resistant PVC materials
3. Continuous and uniform illumination, no LED dots or dark spots; FLAT surface allows various installation environment
4. Environmentally friendly and energy saving
5. Transverse minimum bending diameter: 5cm
6. Easy to install, can be cut and reconnected (connection accessories available)
7. Protection rating IP68

(All joints and connections must be hermetically sealed to achieve IP68)

Application:

Especially suitable for Floor, Stair, Cove Lighting, Signage, Yachts, Accent Lighting, etc. Ideal for Logos, Open Face Letters, Free Form Shapes, Small Border Lighting



SPECIFICATION:

LED Neon Flex F10 (9*18mm)

RED / YELLOW / WHITE / BLUE / GREEN / WARM WHITE

Article No.	C-FR-F10-24/12V-X (X represents color)
LED Type	SMD 3014
Material	PVC-White
Working Voltage	DC24/12V
Rated Power/meter	4W
LED Qty/meter	72LEDs
Lumen/meter	130~150lm (W, WW)
LED Distance	1.389cm
Min. Cutting unit	6LEDs
Min. Cutting length	8.33cm
Max. Connection	20m
IP Rating	IP68

Color temperature available: 2700/3500/4500/5700K

Accessories	Article No.
C-F10-IP68FC	IP68 Clasp front connector without screws, with 30cm cable
C-F10-IP68EC	IP68 Clasp end cap without screws
C-F10-SL-ACH1m	Self Lock Mounting U Channel, 1mtr/pc Aluminum Extrusion, with 3 clasps and 4 screws
C-F10-SL-ACH0.5m	Self Lock Mounting U Channel, 0.5mtr/pc Aluminum Extrusion, with 2 clasps and 2 screws

Separate accessories are available upon request

1m and 3m long Front Connector cable are available

